


NOVOFLEX PUSH MOUNT CABLE TIES



Designed with an additional push mount head these cable ties secure cable looms to a panel or chassis without the need of any other fixing device. The cable tie is fixed by pushing it into a panel of 2.3 mm thickness. Tensioning wings on the side of the head provide extra stability and overcome thickness variations in the wires.




Novoflex Part No.	Nominal Overall length L (mm)	Strap width B (mm)	Thickness (mm)	Push Hole Dia (mm)	Min. Tensile strength (Kg)	Max. Cable Bundle Dia (mm)	Standard Packing
CPM-150	150	3.5	1.4	6.4	9	30	100 Nos.
CPM-160	160	3.5	1.2	4.8	9	35	100 Nos.

Material: Polyamide Standard Colour : Natural White.

NOVOFLEX CABLE TRAY FIXING TIE



Designed to provide a convenient method of fixing cables to perforated cable trays. Supplied as a one piece tie, the two sections can easily be pulled apart and fixed on either side of the trays, thus eliminating the need to access the rear of the tray.
Standard Colour : Natural White & Black.
Operating Temperature : -25°C to +95°C
Tensile Strength : 55 kg




Novoflex Part No.	Nominal Overall length (mm)	Strap width (mm)	Thickness (mm)	Min. Tensile strength (Kg)	Max. Cable Bundle Dia (mm)	Standard Packing
CPT 360	360	7.6	1.2	55	102	100 Nos.

Material: Polyamide

NOVOFLEX RELEASABLE CABLE TIES



Its design features offer alternative degrees of fixing either as a temporary measure prior to completing the wiring process or as a permanent bunching device. For modifications the tie may be released and refastened easily. Ideal for use in places where changes are anticipated. May also be used in the field.
Standard Colour : Natural White & Black..
Operating Temperature : -25°C to +70°C



Novoflex Part No.	length A (mm)	width B (mm)	Max. Cable Bundle Dia (mm)	Standard Packing
ET 80	80	2.5	14	100 Nos.
ET 120	120	2.5	26	100 Nos.



Material: LDPE.

NOVOFLEX BEADED CABLE TIES



The one piece beaded cable ties can be assembled in different ways as per the requirements. The smooth rounded edges of the beads prevent the wires from slipping and being cut by the tie. Reusable, this tie is ideal


for use where wiring modification and repair is required.
Standard Colour : Natural White.
Operating Temperature : -20°C to +70°C




Novoflex Part No.	length A (mm)	width B (mm)	Max. Cable Bundle Dia (mm)	Standard Packing
BT 164 PE	164	4	43	100 Nos.

Material: LDPE.

NOVOFLEX POWER CORD TIES




It provides a new convenience for holding mains cord and Power cords. These are designed for a fast and easy assembly & provide a neat, compact finish. Available in six standard styles for Cable bundle diameters ranging from 14 to 77mm.
Standard Colour : Natural White & Black.
Operating Temperature : -20°C to +70°C



Novoflex Part No.	Length L (mm)	Width W (mm)	Max. Cable Bundle Dia (mm)	Standard Packing
PCT 200	200	8.7	50	100 Nos.
PCT 260	260	8.7	77	100 Nos.
KST 160	160	10	35	100 Nos.
HLT 88	88	6	14	100 Nos.
PLT 210	210	8	45	100 Nos.



Material: LDPE.

NOVOFLEX HOOK AND LOOP Reusable Magic Ties



They secure the cables firmly without damaging the cables. They are releasable & reusable upto 400 times. They provide flexibility in insertion of additional wires in the bundle at a later stage due to changes in planning etc..

Standard Colour : Black. Other colours available subject to MOQ.



Novoflex Hoop-Look Part No.	Length L (mm)	Width W (mm)	Thickness (mm)	Bundle Diameter (mm)	Standard Packing
HLM 130	130	12.5	1.70	35	10 pcs
HLM 180	180	12.5	1.70	51	10 pcs
HLM 205	205	12.5	1.70	59	10 pcs

All dimensions in mm. Subject to technical change. Special size available on request.