


NOVOFLEX MINI CARD SPACER SUPPORT





Mini card spacer supports are designed to support PCB securely by large bottom base. Available in three standard spacing heights of 2.5, 4.0 & 17 mm.
Standard Colour : Natural White
Operating Temperature : -25° C to +85° C.



Novoflex Part No.	Dimensions			Hole Diameter (mm)
	A (mm)	B (mm)	C (mm)	
MCBS 25	2.5	5.3	7.0	3.0
MCBS 40	4.0	5.3	7.0	3.0
MCBS 170	17.0	5.3	5.0	3.0

Material: Polyamide.

NOVOFLEX PC BOARD HOLDER



It is designed to provide permanent locking for chassis. For modification or service, the PCB can be pulled out easily by just pinching the head with finger or simple plier. Snap into 3.2 mm dia hole of 1.6 mm thick chassis & PCB. Available in spacing height 13.3 mm.

Standard Colour : Natural White

Operating Temperature : -25° C to +85° C

Novoflex Part No.	Dimensions			Standard Packing
	A (mm)	B (mm)	C (mm)	
PCBH 133	13.3	6.4	5.3	100 Nos.

Material: Polyamide.

NOVOFLEX PCB SUPPORT FOR WOODEN CHASSIS



It is designed to provide spacing between PCB and wooden chassis or fixing PCB to wooden chassis. Available with spacing height 6.4 mm between chassis and PCB.

Standard Colour : Natural White

Operating Temperature : -25° C to +85° C

Novoflex Part No.	Spacing Height	Standard Packing
PCBC 64	6.4 mm	100 Nos.



Material: Polyamide.

NOVOFLEX TURN ON WIRE CONNECTORS



Please email us for detailed specifications.

NOVOFLEX MICRO SUPPORT POST



It is designed to provide permanent locking for chassis. For modification or service the PCB can be pulled out easily by just pinching the head with finger or simple plier. Snap into 3.2 mm dia hole of 1.6 mm thick chassis & PCB. Available in spacing height 11.1 mm.


Standard Colour : Natural White

Operating Temperature : -25° C to +85° C

Novoflex Part No.	Standard Packing
MSPM 111	100 Nos.

Material: Polyamide.

NOVOFLEX TEAR DROP BOARD SUPPORTS



Teardrop style nose simplifies insertion and provides increased holding power. Snap into 2.5 mm dia hole of up to 1.6 mm thick board.


Standard Colour : Natural White.

Operating Temperature : -25° C to +85° C

Novoflex Part No.	Spacing Height (mm)	Dia Hole (mm)	Standard Packing
PSTE 79	7.9	2.5	100 Nos.

Material: Polyamide.

NOVOFLEX ADHESIVE BACKED PCB SUPPORT



It is designed for fixing PCB to chassis in all types of electronic equipments. This PCB support is ideal where there is no possibility of making holes in chassis. PCB is installed just by snapping into the PCB support. Available with spacing of 9.7 mm.

Standard Colour : Natural White

Operating Temperature : -25° C to +85° C.

Novoflex Part No.	A (mm)	Spacing distance A+1(mm)	B (mm)	Standard Packing
PCBA 97	8.7	9.7	17.2	100 Nos.

Material: Polyamide.

NOVOFLEX MID WAY WIRE CONNECTORS



Please email us for detailed specifications.