


NOVOFLEX ADHESIVE BACKED CABLE HANGER CLIP



Designed to secure cables or harnesses where fixing holes are impractical, the snap in action secures the cables and takes minimum assembly time. Installation is easy - just peel off the release paper and press firmly on any clean & smooth surface. Standard Colour : Natural White. Operating Temperature : -25° C to +85° C.




Novoflex Part No.	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Standard Packing
CKA-5	25	25	12.5	20	19.5	100 Nos.

Material: Polyamide.

NOVOFLEX SELF ADHESIVE TWIST CLIP



This clip is designed to lift wires and keep them away from hot components on the board. The adhesive backed clip is installed quickly and wires can easily be routed or rerouted. Standard Colour : Natural White. Operating Temperature : -25° C to 85° C.




Novoflex Part No.	Dimensions			Standard Packing
	A (mm)	B (mm)	C (mm)	
SKA - 5	8.3	10.2	36.8	100 Nos.

Material: Polyamide.

NOVOFLEX PUSH MOUNT WIRE HOLDER



It's a novel means to channel, route, fix, anchor or harness a single or group of bundle of wires for a wide range of usage in electronic, electrical, communication and automobile industry. It can be easily snapped into drilled or punched holes of 4.8 mm diameter in a PCB or metal chassis of thickness from 0.5 mm to 2.3 mm, where it locks firmly and permanently in place. Available in six standard sizes. Standard Colour : Natural White & Black. Operating Temperature : -25° C to +85° C.



Novoflex Part No.	Height H (mm)	Bundle Diameter Range				Hole Dia (mm)	Standard Packing
		A (mm)	B (mm)	C (mm)	W (mm)		
WH 5	9.5	13	5	8.2	11.1	4.8	100 Nos.
WH 10	14.7	18.2	10.2	8.2	11.1	4.8	100 Nos.
WH 19	23.7	27.2	19.2	8.2	11.1	4.8	100 Nos.
WH 27	31.7	35.1	27.1	8.2	11.1	4.8	100 Nos.
WHH 13	15.7	20.2	13.1	12.6	24	4.8	100 Nos.
WHS 20	28.5	31.3	20.5	13.0	20	6.4	100 Nos.

Material: Polyamide.

NOVOFLEX TWIST CLIPS



They provide a new convenience in initial assembly of wires, plus versatility for easy inspection, removal, repair or changing of wires. Wire bundles are secured in moments with a fingertip twist. These clips cut costs by speeding assembly. Available in 5 standard sizes covering cable bundle diameter ranging from 4.0 to 20.3 mm.




Standard Colour : Natural White. Operating Temperature : -25° C to 85° C.

Novoflex Part No.	Bundle Diameter Range	Standard Packing
KK-00	12.0mm - 15.0mm	100 Nos.
KK-0	17.8mm - 20.3mm	100 Nos.
KK-1	10.0mm - 12.7mm	100 Nos.
KK-2	7.6mm - 10.0mm	100 Nos.
KK-3	4.0mm - 7.5mm	100 Nos.


Material: Polyamide.

NOVOFLEX STAND OFF TWIST CLIPS



Designed to lift wires off board to avoid hot components and minimize transient interference. Cable & wire bundles can be secured simply by a fingertip twist. The main feature of these clips is that they can be installed easily & quickly by just pushing into a predrilled hole in PCB frame, chassis, sidewall electronic / electrical equipment in moments. Available in 6 standard sizes.


Standard Colour : Natural White. Operating Temperature : -25° C to 85° C.




Novoflex Part No.	Dimension in mm				Hole Dia (mm)	Standard Packing
	A	B	C	D		
SKP-1	24	4.4	10	10	4.76	100 Nos.
SKP-2	27	18	12	10	4.76	100 Nos.
SKP-3	18	31.5	5.5	10	4.76	100 Nos.
SKP-6	30	68	11	12	4.76	100 Nos.
SKP-9	30	2.5	15	12	4.76	100 Nos.
SKP-10	38	13	19	11	6.40	100 Nos.

Material: Polyamide.

NOVOFLEX HINGED TWIST CLIP



It is designed for routing wires to any direction. Simply twist to open and close for wiring change and repairs. It is mounted securely with a single screw. Standard Colour : Natural White.



Novoflex Part No.	Dimensions			Standard Packing
	A (mm)	B (mm)	C (mm)	
SKS-4	8.3	10.2	36.8	100 Nos.

Material: Polyamide.