


**NOVOFLEX ADHESIVE BACKED TIE MOUNTS**



Use these cable tie mounts to anchor wire bundles or cables to walls, ceilings, desks or any other structure. Easy to use and apply in hard to reach places, the cover base adhesive is good to be used under continuous temperatures of 125° F (52° C). The continuous straight pull rated load is 1 lb. per square inch of adhesive.



Novoflex Part No.	Size L X W (mm)	Mounting Method	For Max. Cable Tie Width "A" (mm)	Standard Packing
TC1 (A)	28x28	Adhesive Foam Tape	5.5	100 nos.
TC2 (A)	19x19	Adhesive Foam Tape	4.0	100 nos.
TC12 (A)	12.5x12.5	Adhesive Foam Tape	2.5	100 nos.

Material: Polyamide Standard Colour: Natural White.

**NOVOFLEX SCREW TYPE TIE MOUNTS**



Use these cable tie mounts to anchor wire bundles or cables to walls, ceilings, desks or any other structure. The saddle design provides maximum stability to wire bundles. To apply, simply fix the mount with a screw and secure wire bundles with cable ties.




Novoflex Part No.	Size (mm)	Mounting Method	For Max. Cable Tie Width (mm)	Standard Packing
TC1 (S)	28x28	5 mm Screw	5.5	100 nos.
TC2 (S)	19x19	4 mm Screw	5.5	100 nos.
TC3 (S)	13x12	3 mm Screw	8.5	100 nos.
TC4 (S)	22.5x16	6 mm Screw	8.5	100 nos.

Material: Polyamide. Standard Colour: Natural White

**NOVOFLEX PUSH MOUNT TIE MOUNT**



Use these cable tie mounts to anchor wire bundles or cables to walls, ceilings, desks or any other structure. To use simply push the head of the mount through the hole, fastening the mount there. Then pass the cable tie through the slot provided at the base of the mount.



Novoflex Part No.	Size (mm)	Mounting Method	For Max. Cable Tie Width (mm)	Standard Packing
TC 7 (P)	20x9.5	Push Mount in 6.4 mm hole Dia	8.1	100 nos.

Material: Polyamide. Standard Colour: Natural White.

**NOVOFLEX ADHESIVE BACKED ADJUSTABLE CABLE CLAMP**




It is a one piece pressure sensitive adhesive clamp designed to reduce the time spent on electrical and electronic wiring installation and to provide a system which is absolutely foolproof, simple, safe and permanent in operation. It is widely used for securing wires, cables or fixing and holding capacitors, electronic components or various sizes, diameter and shapes. The Ladder style fastening method can be released and easily

refastened. Can be mounted in two ways using adhesive tape backing or screw - in. Available for Cable bundle diameter ranging from 5 to 35 mm in natural colour.

Standard Colour: Natural White.


Operating Temperature: -25° C to +85° C.



Novoflex Part No.	Mounting Method	Cable Dia Range	A (mm)	B (mm)	C (mm)	D (mm)	Screw Hole dia (mm)	Standard Packing
ACC1 (A)	Adhesive	5 to 21	21	30	12	80	3.2	100 NOS.
ACC1 (S)	Screw	5 to 21	21	30	12	80	3.2	100 NOS.
ACC1 (P)	Push Mount	5 to 35	21	30	11	126	6.3	100 NOS.
ACC2 (A)	Adhesive	5 to 35	21	30	12	126	3.2	100 NOS.
ACC2 (S)	Screw	5 to 35	21	30	12	126	3.2	100 NOS.

Material: Polyamide.


**NOVOFLEX ADHESIVE BACKED FLAT RIBBON CABLE CLAMP**



A practical, fast way to mount any size of flat ribbon cable. These adhesive backed, or screw mounted clips securely hold flat or ribbon cables. Cables can be removed for rerouting or replacement if desired. Can accommodate stacked cables too. Its flexible tension range can hold more than one ribbon cable.

Standard Colour: Natural White.

Operating Temperature: -25° C to +85° C.



Novoflex Part No.	Mounting Method	A (mm)	B (mm)	C (mm)	D (mm)	Standard Packing
FRC (A)	Adhesive	20.50	30.40	25.40	3.50	100 Nos.
FRC (S)	Screw	20.50	30.40	25.40	3.50	100 Nos.

Material: Polyamide.


**NOVOFLEX ADHESIVE BACKED CABLE GUIDE CLIP**



Designed to guide 6.4 mm (1/4") dia RG/U type TV cable. This clip is also used for guiding or fixing cables in electrical / electronic / communication equipments. Available in natural colour with high quality self adhesive backing for quick and permanent installation.

Standard Colour: Natural White.

Operating Temperature: -25° C to +85° C.



Novoflex Part No.	Mounting Method	Max Cable Tie Width	Standard Packing
TVCG 1 (A)	Adhesive	6.4 mm	100 Nos.

Material: Polyamide.