


## NOVOFLEX Turn on Wire Connector



Quick, easy and secure way to connect wires together.  
Material: PVC - Threaded, Heat Resistant & Insulating.  
Operating Temperature : -20° C to + 85° C

### How To Use :

1. Turn Power off before installing or removing terminal.
2. Strip wire insulation 1/2".
3. Firmly grasp wires, making sure insulation ends are even and tightly bundled. ( Wires may be twisted or untwisted.) Lead stranded wires slightly. Slip the connector over wire tips.
4. Turn connector onto wires in clockwise direction until secure.
5. To remove, turn connector counter - clockwise.

NOVOFLEX Turn on Wire Connector						
Novoflex Part No.	H	W	D	Colour	Suggested Wire A.W.G.	Standard Packing
TWC - 1	14.7	8.5	6.0	Grey	22 - 16	100 Nos
TWC - 2	17.5	10.1	7.5	Blue	20 - 16	100 Nos
TWC - 3	21.4	11.2	8.2	Orange	20 - 16	100 Nos
TWC - 4	23.6	13.7	10.5	Yellow	18 - 14	100 Nos
TWC - 5	26.5	16.0	13.0	Red	14 - 10	100 Nos

## NOVOFLEX Quick (Mid Way) Wire Connectors


For quick connection of two wires without stripping the wires.

Material : Nylon

Operating Temperature : -20°C to + 85° C

### How To Use :

1. Insert wires on the grooves of the connector.
2. Clamp down the plastic body.
3. The two wires gets connected.



### NOVOFLEX Quick (Mid Way) Wire Connectors

Novoflex Part No.	Suggested Wire		Colour	Dimensions mm		Standard Packing
	mm <sup>2</sup>	A.W.G.		W	L	
MC - 1	0.5 - 1.5	22 - 16	Red	20	32	100 Nos
MC - 2	1.5 - 2.5	16 - 14	Blue	20	32	100 Nos
MC - 3	4.0 - 6.0	12 - 10	Yellow	20	32	100 Nos

## NOVOFLEX Expand Plugs



Used primarily for light duty fastening of screws in concrete, brick, dry wall, hollow brick, wooden structure, natural stone plates.

Quick & secure tool for fixing screws.

Material: PE - elastic and shock resisting.

### How To Use :

1. Drill a hole in the wall / wood.
2. Drive in the Expand Plug.
3. Drive the screw in clockwise direction.
4. Plug expands, locks the screw firmly ensuring high grip.

NOVOFLEX Expand Plugs				
Novoflex Part No.	L mm	D mm	d mm	Standard Packing
EP - 6	31	6	4.8	100 Nos
EP - 8	40	8	6.0	100 Nos
EP - 10	45	10	7.5	100 Nos
EP - 12	48	12	6.5	100 Nos

