

Twist Lok Ties



Novoflex Twist Lok Ties are designed for use in a diverse range of packing and tying applications where secure but provisional fastening is required. These ties have found successful use in a wide spectrum of industries such as electrical, electronic, agriculture, food, packaging, etc. They are available in various product lengths as well as in rolls of 100 metres.

Material: GI Core with a PVC Coating.

Flammability Rating: UL94 V-2.

Standard Colours: Titanium White & UV Resistant Black (B)

Continuous Operating Temperature: -25° C to +70° C.

Storage Conditions: To be stored in a cool, dark, dry place away from sunlight in a sealed condition.

Example Applications: Couriers & Logistics, Pharmaceutical & Drugs, Chemicals & Dyes, Telecom, Consumer Durables, Computers & Networking, Food Processing, Electronics, Control Panels, New Project Installations, Domestic Use and many more.

NOVOFLEX - Twist Lok Ties

Novoflex Part No.	Length (mm)	Width (mm)	Thickness (mm)	Standard Packing (Nos.)
TL 100	100	4	0.85	100
TL 150	150	4	0.85	100
TL 200	200	4	0.85	100

NOVOFLEX - Twist Lok Ties in Roll Form

Novoflex Twist Lok Ties are designed for use in a diverse range of packing and tying applications where secure but provisional fastening is required. These ties have found successful use in a wide spectrum of industries such as electrical, electronic, agriculture, food, packaging, etc. Twist Lok Ties also come in a continuous roll form of 100 metres. Simply cut the lengths according to your requirements, and get on-site, tailor-made ties, which are just perfect for your needs. It is useful in situations where changes are anticipated; requirements are in varying sizes, or where requirements cannot be predicted in advance.

Novoflex Part No.	Length (mtrs)	Width (mm)	Thickness (mm)	Standard Packing (Mtrs.)
TL M	100	4	0.85	100

