

Strain Relief Cord Bushing



Novoflex Strain Relief Cord Bushing are designed to protect the lifeline of electrical and electronic appliances, equipment, and machine tools by absorbing various twist, pull, push and flex actions on power supply cords. They are installed easily by firmly squeezing the cord bushings on power cables and pushing them into the sheet metal holes or other entry points thereby securely anchoring, insulating and protecting the power cords. These bushings eliminate the need to tie or knot cords within the cabinets or enclosures and increase the life span of the entire system exponentially.

It is recommended to firmly close the bushings with pliers on the cables before insertion into the holes to ensure a firm grip.

Material: **Nylon 6.** Resistant to Fungus, Corrosion, and most mild acids.


Flammability Rating: **UL94 V2.**

Standard Colour: **UV Resistant Black.**


Operating Temperature: **-25° C to +85° C.**

Storage Conditions: To be stored in a cool, dark, dry place away from sunlight in a sealed condition.


Example Applications: Railways, Ship Building, Telecom, Consumer Durables, Computers & Networking, Electric Metering, Electronics, Control Panels.



TOP VIEW



FRONT VIEW



SIDE VIEW

NOVOFLEX - Strain Relief Cord Bushing

Type	Novoflex Part No.	Length A (mm)	Width B (mm)	Panel Thickness C (mm)	Panel Hole Dia D (mm)	App. Wire Dia (mm)	Standard Packing (Nos)
Flat	SBF 21	10.4	8.2	1.6	8.8	2.3 to 4.5	100
	SBF 32	10.4	10	2.4	9.8	3.0 to 5.6	100
	SBF 41	13	12.7	2.6	12.5	3.0 to 7.1	100
Round	SBR 51	11	11.4	2	11	6.4 to 7.4	100
	SBR 52	11.2	10.8	2.5	12	6.4 to 7.4	100
	SBR 62	14.4	13.4	3.3	14.1	7.4 to 8.2	100
	SBR 71	14.4	13.3	3.3	14	8.2 to 9.4	100
	SBR 72	19.2	16.3	3.4	17.5	8.2 to 11.0	100
	SBR 80	19.9	19.1	1.4	21.1	11.0 to 12.0	100
	SBR 82	20.2	20.3	3.5	21.1	12.0 to 15.2	100

