

Flexiform Continuous Grommet Strip



Novoflex Flexiform Continuous Grommet Strip is a low cost, cut-to-fit strip that protects cables and wires from sharp panel edges and knock-outs. It is the best method of protecting cables from chaffing where they pass through panel apertures. Ideal for all shapes and sizes of holes, especially for odd sizes, on any type of panel material including wood, steel, aluminium, perspex and glass. It is applied by hand without the aid of tools or adhesive and eliminates the need for varied diameter grommet rings.

Available in serrated and non serrated variants.

Material: LDPE Resistant to Fungus, Corrosion, and most mild acids.


Flammability Rating: UL94 V-2

Standard Colour: Natural White.

Operating Temperature: -20° C to +85° C

Storage Conditions: To be stored in a cool, dark, dry place away from sunlight in a sealed condition.

Example Applications: Telecoms equipment, switchgear and control cabinets.



NOVOFLEX - Flexiform Continuous Grommet Strip					
Novoflex Part No.	Colour	Panel Thickness (mm)	Panel Thickness (SWG)	Minimum Dia (mm)	Standard Packing (Mtr)
GSP 30 (PE)	Natural Colour	1.5 – 3.0	17 - 11	25	50
GSP 45 (PE)	Natural Colour	3.0 – 4.5	11 - 7	30	50
GSP 60 (PE)	Natural Colour	4.5 – 6.4	6 - 4	35	50
GS 45 (PVC)	Black	3.0 – 4.5	11 - 7	30	50
GSS 45 (PVC)	Black	3.0 – 4.5	11 - 7	30	50
GSS 60 (PVC)	Black	4.5 – 6.4	6 - 4	35	50